






- Fast installation range of speaker
- Full range yet high quality music and speech reproduction



MODEL	CP-506	CP-606	CP-810
Power at 100V	3/6W	3/6W	5/10W
Power at 70V	1.5/3W	1.5/3W	2.5/5W
SPL(1W/1M)	92dB	92dB	92dB
Max SPL@ 1M	99dB	99dB	101 dB
Freq. Response	100Hz-16KHz	100Hz-18KHz	100Hz-18KHz
Cutout Size	Dia 150mm	Dia 170mm	Dia 210mm
Product Size	Dia 175x60mm(H)	Dia 185x75mm(H)	Dia 230x90mm(H)
Installation	Inceiling	Inceiling	Inceiling
Enclosure Material	ABS	ABS	ABS
Weight	0.5Kg	0.7Kg	1Kg
Finish	White	White	White
Speakers	5"x1 full range	6"x1 full range	8"x1 full range

4.5 inch Ceiling speaker



MODEL	CP-506IH
Driver size	4.5 inch
Rated Power in 100	6W/3W
Rated Power in 70	3W/1.5W
Sensitivity	90Db±2(1w/1M)
Max SPL	96Db
Speaker impedance	8Ω
Frequency range	105Hz-18KHz
1000Hz Dispersion angel	145 degree
Size	Φ 174X87MM
Hole cut size	Φ 148MM
Material	ABS
Color	White
Installation	In ceiling