

LS PAR 1512-W

Model: PR-6207



RoHS | CE | LED | 1.5m | IP67 | T_c150°C | T_a40°C | 

LS PAR 1512-W is a new launched exterior par, rating IP67. It's equipped with PHILIPS 12 pcs of 15W LEDs, provides pure white light, ideal for multi-scale outdoor stages, buildings, theme parks, etc.

IP67, 12x15W



Scan with your Phone
to view more detail



10Kg
Size(mm)

Specifications

- Input Voltages
100-240V AC, 50/60Hz
- Power Consumption
180W@220V
- Light Source
PHILIPS 12x15W LEDs white, 50,000 hrs
- Strobe
Electronic strobe, 0.5-33 F.P.S
- Dimmer
0-100% linear adjustment
- Colors
White
- Light Angle
Beam angle(1/2 peak) $\theta_{1/2}$: 14°(optional 10°, 20° and 40°)
- Control
International DMX512, 3 pins interface
Standard mode 2 channels
Master-slave mode, test mode
DMX control mode, preset memory and user memory
- Other Functions
LED board temperature and fixture usage time can be checked via menu
DMX channel mode and settings displayed
LED and inverted display
Display backlight automatically shut off after delay
Transmitted under synchronization
- Physical
Housing: high intensity cast aluminum alloy, IP67
Ambient working temperature: -20°C~40°C
- Weight
Net weight: 10kg
- Packaging
Standard: carton 475x395x380(mm)
Optional: flight case
- Accessories
C clamp, 1 pc
Signal adapter cord, 2 pcs
Power cord, 1 pc
Safety cord, 1 pc
Optional: N/A

