# Pro Convert HDMI TX Technical Specifications

Copyright (c) 2011–2026 Nanjing Magewell Electronics Co., Ltd. All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

HDMI, the HDMI logo and High-Definition Multimedia interface are trademarks or registered trademarks of HDMI Licensing LLC. NDI® is trademark or registered trademark of Vizrt NDI AB.

Revised on 10/09/2026

## Input Features

- Max video input: 2048x1200 60fps 4:4:4/4:2:2
- Input video at any format by custom EDID of input port
- Video formats: RGB, YUV BT.601/709/2020
- 8-channel HDMI-embedded audio
- HDMI interface: HDMI 1.4, DVI-D

## NDI® Encoding Features

- Encoding NDI High Bandwidth real-time stream at up to 2048x1200 60fps 4:2:2 8-bit.
- Output the same resolution as input or any custom resolution. Typical outputs include:
  - 2048x1080p/1920x1080p 23.98/24/25/29.97/30/50/59.94/60
  - 1920x1080i 25/29.97/30/50/59.94/60
  - 1280x720p 23.98/24/25/29.97/30/50/59.94/60/100/119.88/120
  - 720x480p/720x480i 59.94/60/119.88/120
  - 720x576p/720x576i 50/100
- Output frame rate same as the original, 1/2, 1/3 or 1/4 of input frame rate
- Encoding 2-channel NDI-embedded audio
- Support NDI 6.3

## Configuration Management

- Register with Control Hub
- Remote control via WebUI and Control Hub
- Provide comprehensive information regarding the device and input signals in real-time
- Allow to configure how an input is processed and encoded, including deinterlacing, EDID, up/down scaling, frame rate, aspect ratio, as well as the network connection
- Update firmware
- Support USB RNDIS/ECM
- Support IE/Edge/Firefox/Chrome/Safari/Opera web browsers
- Provide HTTP APIs

## On-board Control Buttons

- 16 Position Rotary DIP Switch: set board-index from 0 to F

## PTZ Control

- Control PTZ cameras using protocols of VISCA, Visca UDP, Visca UDP2rs232, PELCO-P and PELCO-D via NDI
- Mini-DIN–8 jack (shared with Tally light)

## Network Interfaces

- 10/100/1000Mbps Ethernet
- IEEE 802.3af PoE

## USB Interface

- USB2.0 Type B

    - 5V/2.1A power supply
    - USB RNDIS/ECM

## Supported Products

- NDI Studio Monitor
- OBS
- vMix
- Any other NDI-enabled product

## LED Indicators

- Status LEDs indicate:
    - Power supply: on/off
    - Input signal: locked/unlocked

## Form Factor

- 100.9smm (L) x 60.2mm (W) x 23.3mm (H)

## Accessories

- USB 2.0 A to B cable
- 5V/2.1A power adaptor
- Mini-DIN 8 breakout cable
- Tally light
- L-bracket

## Screw Mounting Hole

- ¼–20 threaded hole

## Power Consumption

- 5V max current: ~1.5A
- Max power consumption: ~6W

## Working Environment

- Operating temperature: 0 to 40 deg C
- Storage temperature: –20 to 70 deg C
- Relative humidity: 5% to 90% non-condensing