

Front View



Side View

vue UHD PTZ

The vue UHD PTZ boosts HDMI/RTSP output resolution to 4K@60Hz. It supports real-time AI tracking of faces/figures/zones and incorporate a new USB 3.0 output port to meet growing demands for remote conferencing and live streaming applications.

Notably, the NDI version has been upgraded from NDI|HX to NDI|HX3, delivering enhanced video quality and lower latency for network streaming - addressing professional users' pursuit of superior performance. The front panel features an OLED screen displaying real-time resolution and IP information for better camera management.

Like its vue 4K sibling which boasts a unique 360°-visible TALLY indicator and identification board (immune to device switching interference), the innovative RGBlink vue camera design with patented technology adapts seamlessly to any environment. It utilizes cutting-edge UHD CMOS sensors with AI processing chips for exceptional performance.

Key Features

- 4K60 image with Sony 1/2.8-inch 8.42MP sensor
- 12X/20X/30X optical zoom lenses available
- 16X digital zoom times for sharper details and extended viewing range
- Advanced autofocus for fast, accurate, and stable focusing
- Low-noise CMOS with 2D/3D noise reduction for high SNR and clarity
- High-speed USB 3.0, HDMI, LAN, SDI (1080P60@100m)
- H.265/H.264 video and AAC/G.711A audio compression up to 4K@60fps
- AAC audio input (16k-48kHz) and G.711A (8kHz) support
- ONVIF/RTSP/RTMP protocols and VISCA control
- AI tracking with face/human recognition for classrooms and meetings
- RS485/RS232 control (RS232 supports cascading)
- Integrated PoE+ and NDI|HX3 for IP workflow and high-quality streaming.
- VISCA/PELCO-D/P protocols with auto-detection
- Silent gimbal with precision stepper motor for smooth, quiet operation
- Low-power sleep mode under 400mW
- 255 presets (10 accessible via remote)
- Infrared remote controller (anti-interference, signal passthrough)
- Ideal for education, conferences, medical, court, and command systems

Specification

Connectors	Video	HDMI, 3G-SDI, LAN (PoE+), USB3.0	
	Control	RS-232	Loop-through RS232 output
		RS-485	
	Audio input	Line-in	Dual-channel 3.5mm audio jack
	Audio output	HDMI, 3G-SDI, LAN (PoE+), USB3.0	
	LAN	1000M Ethernet port with POE+ power supply, supports audio/video output and IP VISCA control protocol	
Standard	Image bitstream	Dual stream output capability	
	Video compression format	LAN	H.264/H.265
		USB 3.0	MJPG/H.264/H.265/YUY2/NV12
	Control protocol	VISCA/Pelco-D/Pelco-P	
		Baud rate: 115200/9600/4800/2400bps	
	Audio compression format	AAC， G.711A	
	Network protocol	Support RTSP, RTMP, ONVIF, SRT, NDI (optional); Network VISCA control protocol supported	
		Remote firmware upgrade, reboot and reset supported	
	USB communication	UVC (USB Video Class) and UAC (USB Audio Class) compliant	
Len Parameters	Image sensor	1/2.8-inch high-quality CMOS sensor	
	Effective pixels	8.42 megapixels, 16:9 aspect ratio	
	Video signal format and resolution	HDMI	3840 × 2160P@60/59.94/50/30/29.97/25 | 1920 × 1080P@60/59.94/50/30/29.97/25 | 1280 × 720P@60/59.94/50
		SDI	1920 × 1080P@60/59.94/50/30/29.97/25 | 1920 × 1080I@60/50/59.94 | 1280 × 720P@60/59.94/ 50
		USB	**YUY2/NV12:** 1920 × 1080 | 1280 × 720 | 1024 × 576 | 800 × 600 | 800 × 448 | 640 × 480 | 640 × 360 | 480 × 270 320 × 180P@30/25/20/15/10/5fps
			H264/H265/MJPG: 3840 × 2160 | 1920 × 1080 | 1600 × 896 | 1280 × 720 | 1024 × 576 | 960 × 540 | 800 × 600 | 800 × 448 | 720 × 576 720 × 480 | 640 × 480 | 640 × 360 | 480 × 270 | 352 × 288 | 320 × 240@60/30/25/20/15/10/5fps
		LAN	**H264/H265:** Main Code Stream 3840 × 2160 | 2592 × 1944 | 2304 × 1296 @60/30/25/20/15/10/5fps 1920 × 1080 | 1280 × 720@60/30/25/20/15/10/5fps Subcode Stream 1920 × 1080 | 1280 × 720 | 640 × 360 | 640 × 480 | 320 × 240 | 320 × 180@30/25/20/15/10/5fps

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgblink.com
Headquarter: 6th Floor, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China


Specifications are correct at time of printing and subject to change or alteration without notice.

Len Parameters	Optical Zoom	12x	20x	30x
	Digital Zoom	16x	16x	16x
	EFL (f)	f = 4.1 ~ 49.2mm	f=4.8 ~ 96mm	f=5.2 ~ 148.4mm
	H FOV°	70.4°~6.72°	60.04°~3.81°	58.1°~2.14°
	F-Number (F/No.)	F1.8 ~ F2.68	F1.8 ~ F2.9	F1.3 ~ F4.8
	Minimum Illumination	0.5Lux(F1.8, AGC ON)		
	Digital Noise Reduction	2D & 3D digital noise reduction		
	White Balance	Auto/manual/one-click white balance/specified color temperature (2400K-7100K, 100K step)		
	Focus	Auto/manual/one-press focus		
	Iris	Auto/manual		
	Electronic Shutter	Auto/manual		
	Backlight Compensation	On/off		
	Wide Dynamic Range	Off/dynamic level adjustment		
	Video Adjustment	Brightness, sharpness, saturation, contrast, white balance, anti-flicker, low-light compensation adjustable		
	Signal-to-Noise Ratio	>50dB		
Pan-Tilt Parameters	Pan Rotation	-170° ~ +170°		
	Tilt Rotation	-30° ~ +90°		
	Pan Control Speed	0.1°/s ~ 60°/s		
	Tilt Control Speed	0.1°/s ~ 30°/s		
	Preset Speed	Pan: 60°/s, Tilt: 30°/s		
	Number of Presets	Users can set up to 255 preset positions (10 via remote control)		
Other Parameters	Power adapter	Input: AC110V-AC220V		
		Output: DC12V/2.5A		
	Input voltage	DC12V±10%		
	Input current	1.5A (Max)		
	Power consumption	18W (Max)		
	Storage temperature	-10℃ ~ +60℃		
	Storage humidity	20% ~ 95%		
	Operating temperature	-10℃ ~ +50℃		
	Operating humidity	20% ~ 80%		
	Dimensions	167×152×210 mm (6.6x6.0x8.3 in)		
	Net weight	1.9kg (4.2lb)		
	Operating environment	Indoor		
	Remote maintenance	Firmware upgrade, reboot, reset		
	Optional accessories	Mounting bracket, control console		

Product Code

Product Code	Item
981-1100-07-0	RGB12X-UPAI-OL (3G) 4K60 12X POE Tracking Camera
981-1100-08-0	RGB12X-UNAI-OL (3G) 4K60 12X POE NDI Tracking Camera
981-1100-09-0	RGB20X-UPAI-OL (3G) 4K60 20X POE Tracking Camera
981-1100-10-0	RGB20X-UNAI-OL (3G) 4K60 20X POE NDI Tracking Camera
981-1100-11-0	RGB30X-UPAI-OL (3G) 4K60 30X POE Tracking Camera
981-1100-12-0	RGB30X-UNAI-OL (3G) 4K60 30X POE NDI Tracking Camera


Dimension




unit：mm

Installation

Wall Mount



Ceiling Mount



Note: the accessories are not included in the package.

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgblink.com
Headquarter: 6th Floor, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Specifications are correct at time of printing and subject to change or alteration without notice.

RGBlink®
www.rgblink.com