NDPG WM
NDP series
Network Wall-mount Dimmer with RCBO




The **network dimmer pack NDPG WM** is designed to fulfill all the top requirements of the most demanding lighting applications e.g. **theatres**, live concerts and also permanent installations. Unit was especially created for users requiring maximum flexibility, top class features and superb network connections.

Unit is controlled by a high speed processor with smooth **16-bit dimming** resolution via specially designed zero-crossing circuit. This technology guarantees trouble–free operation and high proof against the influence of negative surroundings with top class **rise-time of 400us**.

Moreover, the **network dimmer pack NDP12** comes with **NDP-DC+RELAY** feature that is a **DC DRIVE/RELAY switch with rating of 16A and possibility to turn on/off via curve**. (DC-RELAY is not available for NDP dimmers 25 and 32A).

Every output features its own **combination of MCB and RCD 30mA (TypeA)**

All NDPseries dimming units are covered by a 5-year warranty.



Main voltage: **3x230V / 400V / 40-65Hz**
Main current: **3x20 up to 3x63A**
Protection: **RCBO = Combined RCD 30mA + MCB**

- **DCdrive/pulse** driving of triacs
- **RELAY/DIMMER** on single channel - depends on curve
- **Theater** or touting application
- **Rise-time of 400us**
- **Main switch** per unit
- **RCBO** on each channel
- Double **DMX input + RDM support**
- **Ethernet connection / Art-Net / SRS.net / sACN**
- Software patch of **Manual / DMX A / DMX B / Ethernet**
- **Preheat** for all or a separate channel
- **Free monitoring software**
- **100% duty cycle**

Dimensions: **483 x 460 x 132mm** (WxHxD)

SRS Group s.r.o reserves the right to make changes to the equipment described in this manual/datasheet without prior notice. (E&OE). © SRS Group s.r.o

SRS Group s.r.o.
Pri majeri 4, 831 07 Bratislava, Slovakia
phone: +421 232 661 800, email: sales@srs-group.com, www.srs-group.com

Variants

12-channel version

- *932064* NDPG1210B-5 WM 30mA — 12x10A / 2.3kW, RCBO C10A
- *932065* NDPG1213B-5 WM 30mA — 12x13A / 3kW, RCBO C13A
- *932066* NDPG1216B-5 WM 30mA — 12x16A / 3.7kW, RCBO C16A

6-channel version

- *932067* NDPG6010-5 WM 30mA — 6x10A / 2.3kW, RCBO C10A
- *932068* NDPG6013-5 WM 30mA — 6x13A / 3kW, RCBO C13A
- *932069* NDPG6016-5 WM 30mA — 6x16A / 3.7kW, RCBO C16A

DMX connector


3-pin XLR


5-pin XLR

DDP/NDP output


K0: 6x PG21


K1: 1x HARTING 24 (PH:1-12, N:13-24)


K2: 2x HARTING 16 (PH:1-6, N:9-14, NC:7+8+15+16)


K3: 2x Socapex 19


K4: 12x French Schuko


K5: 12x Schuko


K7: 12x Danish socket


K8: 12x Swiss Socket Type23


K9: 4x HARTING 16 (PH:1-6, N:9-14, NC:7+8+15+16)


K10: 2x HARTING 16 (PH:1,3,.., N:2,4,..., NC:13-16)


K11: 2x HARTING 6


K12: 2x HARTING 6 (PH, N - in round)


K13: 12x CEE16/3p


K14: 6x CEE32/3p

3PH-IN connector


32A 5-pin


63A 5-pin

3PH-IN cable options


1,5m regular cable, open end


2,0m cable, open end


Extra charge for 0.5m power cable 5G6


Extra charge for 0.5m power cable 5G10

SRS Group s.r.o reserves the right to make changes to the equipment described in this manual/datasheet without prior notice. (E&OE). © SRS Group s.r.o

SRS Group s.r.o.
Pri majeri 4, 831 07 Bratislava, Slovakia
phone: +421 232 661 800, email: sales@srs-group.com, www.srs-group.com